updated 2018.10.17 *send updates to: kkopf@hzdr.de*	Wavelength (um)		Frequency (THz)		Avg. Power (W)		Peak Power	Micpulse Energy (µJ)		Pulsewidth	Bandwidth	Peak	Optimal Lasing	Repetition Rate		User Operations/Facilities			undulator and optical cavity				Energy (MeV)	bunch charge (pC)	e- Beam		I average (mA)	I macropulse (mA)	Types of Measurement Capabilities	Other Notes of Interest	First Lasing	Location	website / source	updated 2018.10.17 *send updates to: kkopf@hzdr.de*
	min	max	min	max	typical	max	max (kW)	typical	max	min (ps)	Δλ/λ (%)	Field (MV/cm)	Wavelength (um)	Micropulse	Macropulse	User Ops	Operational	High Field Magnets	Period (mm)	# of periods	K (range)	cavity type		emittance									
FELIX-1	25	140	2	12	0.4	0.8	10^4	5	25	1 - 20	0.3 - 2 (rms)	close to diffraction limited		25 MHz / 1 GHz	10 Hz	16/5	YES	≤ 35 T (static)	65		0.4 - 2.0	free space	15 - 25					200 @ 1GHz	(i) gas-phase (bio-) molecular, cluster and ion (action) spectroscopy (ii) nonlinear, time resolved spectroscopy in the condensed phase at low temperature and /or high magnetic field	three beamlines can be operated simultaneously (FELIX-1 or FELIX-2 and FLARE and FELICE)	1991	Nijmegen, The Netherlands	http://www.ru.nl/felix/	**FELIX-1**
FELIX-2	3	45	6.7	100	0.7	1.5	10^5	10	50	0.25 - 10	0.2 - 3 (rms)	close to diffraction limited		25 MHz / 1 GHz	10 Hz	16/5	YES	≤ 35 T (static)	65		0.4 - 1.9	free space	25 - 45					200 @ 1GHz	(i) gas-phase (bio-) molecular, clustere and ion (action) spectroscopy (ii) nonlinear, time resolved spectroscopy in the condensed phase at low temperature and /or high magnetic field	three beamlines can be operated simultaneously (FELIX-1 or FELIX-2 and FLARE and FELICE)	1992	Nijmegen, The Netherlands	http://www.ru.nl/felix/	**FELIX-2**
FLARE	100	1700	0.2	3	0.2	2	100	1	5	20 - 300	0.3 - 1 (rms)	close to diffraction limited		60 MHz / 3 GHz	10 Hz	16/5	YES	≤ 35 T (static)	110		0.5 - 3.4	waveguide	11 - 17					600 @ 3GHz	nonlinear, time resolved spectroscopy in the condensed phase at low temperature and /or high magnetic field	three beamlines can be operated simultaneously (FELIX-1 or FELIX-2 and FLARE and FELICE)	2011	Nijmegen, The Netherlands	http://www.ru.nl/felix/	**FLARE**
FELICE	5	100	3	60	intra-	cavity	2 x 10^6	200	1000	0.3 - 15	0.3 - 3 (rms)	close to diffraction limited		16 MHz / 1 GHz	10 Hz	16/5	YES		60		0.4 - 1.7	free space	18 - 45					200 @ 1GHz	gas-phase (bio-) molecular, cluster and ion (action) spectroscopy	three beamlines can be operated simultaneously (FELIX-1 or FELIX-2 and FLARE and FELICE)	2007	Nijmegen, The Netherlands	http://www.ru.nl/felix/	**FELICE**
ENEA Frascati (mmW FEL)	2000	3500	0.086	0.15	0.01	0.05	5	0.15		60	0.6 - 8	0.01	2600	3 GHz	4 µs macropulse 10 Hz		YES		25	8	1	waveguide	2.3	90	60 mm mrad			300	studies of biological effects on cells and model membranes, reflective near-field imaging/microscopy	Electron-transparent mirrors (gold coated tungsten wire grids) allow for a compact optical resonator	1991	Frascati, Italy	http://www.frascati.enea.it/fis/lac/fel/fel2.htm	**ENEA Frascati (mmW FEL)**
ENEA Frascati (FEL-CATS)	400	800	0.4	0.7	0.02	0.04	20	0.3		15	10	close to diffraction limited	780	3 GHz	5 µs macropulse 1 Hz		NO		25	16	0,5 - 1,4	N/A	2.5	75				250		single-pass super-radiant FEL allows for a very compact source (2m overall length)	2003	Frascati, Italy	http://www.frascati.enea.it/fis/lac/fel/fel2.htm	**ENEA Frascati (FEL-CATS)**
CLIO	5	150	2	60			100000		100	1 - 10	0.2 - 1			62.5 MHz	10 µs macropulse 25 Hz		YES		50				10 - 41					80	two-color lasing possible 5 - 40 µm		1992	Orsay, France	http://clio.lcp.u-psud.fr/spip.php?rubrique2	**CLIO**
NovoFEL-1	90	240	1.25	3.3	80	500	500	15	50	100	0.3-1		130	5.64/22.56 MHz	CW	12/4	YES	≤ 5 T (static)	120		0 - 1.1	free space	10.8-13.2				8/30		Imaging, spectroscopy, one-pulse high-resolution spectroscopy, ellipsometry, pump-probe, low-temperature, holography, NMR, plasmonics, transformation of wave-beam front, biology study, nano- and microparticle study, continuous optical discharge, combustion and detonation, mass-spectroscopy, atmosphere study, material study	FEL driven by Energy Recovery Linac (ERL)	2003	Novosibirsk, Russia	http://ssrc.inp.nsk.su/CKP/NovoFEL3/	**NovoFEL-1**
NovoFEL-2	35	80	3.75	8.6	80	500	2000	10	60	50	1 - 2		50	7.52 MHz	CW	12/4	YES	≤ 5 T (static)	120		0 - 1.4	free space	20 - 24				8		FEL driven by two-turn ERL		2009	Novosibirsk, Russia	http://ssrc.inp.nsk.su/CKP/NovoFEL3/	**NovoFEL-2**
NovoFEL-3	5	15	20	60	10	100		3	30	10	1 - 2		8	3.76 MHz	CW	12/4	YES	≤ 5 T (static)	60		0.3 - 2.5	free space	40-44				4		FEL driven by four-turn ERL		2015	Novosibirsk, Russia	http://ssrc.inp.nsk.su/CKP/NovoFEL3/	**NovoFEL-3**
FELBE (U27)	4	21	14.3	75	5	20	1MW	0.4	1.5	0.8	0.5 - 5	7	81	13 MHz	CW 1 - 25 ns single-shot	24/1	requested by users	≤ 20 T (pulsed) ≤ 8 T (static)	27		0.5 - 0.7	free space	15 - 35	77			1.6	1.6	pump-probe, s-SNOM, low-temp, high field, low temperature, time-resolved spectroscopy, primarily solid-state material physics, low-dimensional materials and structures, correlated systems, plasmonics	2 modulator sections separated by a variable path distance	2006	Dresden, Germany	https://www.hzdr.de/FELBE	**FELBE (U27)**
FELBE (U100)	18	250	1.2	16.5	10	65	5000	0.7	5	1	0.5 - 5	0.6	80	13 MHz	CW 1 - 25 Hz single-shot	24/7	YES	≤ 70 T (pulsed) ≤ 8 T (static)	100	38	0.5 - 2.8	partial parallel plate waveguide	15 - 35	77			1.6	1.6	pump-probe, s-SNOM, low-temp, high field, low temperature, time-resolved spectroscopy, primarily solid-state material physics, low-dimensional materials and structures, correlated systems, plasmonics		2006	Dresden, Germany	https://www.hzdr.de/FELBE	**FELBE (U100)**
FELBE (U37)	5	40	7.5	60	7	45	3750	0.5	3	0.8	0.5 - 5	10 (TBD)	10	13 MHz	CW 1 - 25 Hz single-shot	24/7	YES	≤ 70 T (pulsed) ≤ 8 T (static)	37	54	0.4 - 1.35	free space	15 - 35	77			1.6	1.6	pump-probe, s-SNOM, low-temp, high field, low temperature, time-resolved spectroscopy, primarily solid-state material physics, low-dimensional materials and structures, correlated systems, plasmonics		2017	Dresden, Germany	https://www.hzdr.de/FELBE	**FELBE (U37)**
ALICE	5	9	33.3	60			600		0.6	1	0.9 - 1.8			16.25 MHz	85 µs macropulse 10 Hz		YES						27.5						Dedicated for medical/biological studies	FEL driven by Energy Recovery Linac	2010	Daresbury, Great Britain	https://www.astec.stfc.ac.uk/Pages/ALICE-free-electron-laser.aspx	**ALICE**
TARLA-1														11 MHz		planned under construction			30				15 - 40 (target)						Commissioning planned for 2018			Ankara, Turkey	http://tarla.org/en/	**TARLA-1**
TARLA-2														13 MHz		planned under construction			30				15 - 40 (target)						Commissioning planned for 2018			Ankara, Turkey	http://tarla.org/en/	**TARLA-2**
FHI	2.9	50	6	103						≤ 1				1 GHz	1 - 15 µs macropulse 20 Hz		YES		40		0.5 - 1.6		18.5 - 43.5								2012	Berlin, Germany	http://fel.fhi-berlin.mpg.de/Main/HomePage	**FHI**
s-DALINAC	no up to date information available about current status																???															Darmstadt, Germany	https://www.fkp.tu-darmstadt.de/fachbereich_fkp/index.en.jsp	**s-DALINAC**
Israeli FEL (THz/THz)	200	1000	0.3	1.5										3 GHz		under construction			6										Experiments to be driven by an RF photoinjector		2018 (planned)	Beer Sheva, Israel		**Israeli FEL (THz/THz)**
Israeli FEL (mmW)	2725	3156	0.095	0.11						1-50E+06	1.30E-04			N/A	1 - 50 µs ??? Hz		???		44.4				1.35 - 1.45					700 - 3000		FEL driven by an Electrostatic accelerator			Ariel, Israel	http://www.ariel.ac.il/research/fel	**Israeli FEL (mmW)**
UCSB - FIR FEL	63	338	0.89	4.76			6			1.0E+06	0.007			N/A	1 - 20 µs 0 - 2 Hz single-shot	by request	YES	≤ 8 T (static) ≤ 12. 5T (static)	20		0.132	parallel plate waveguide	2.5 - 6					2000	FEL driven by a recirculating Electrostatic accelerator cavity dumping currently not available		1989	Santa Barbara, CA USA	http://www.mrl.ucsb.edu/terahertz-facility/instruments/ucsb-free-electron-laser-source	**UCSB - FIR FEL**
UCSB - mmW FEL	338	2500	0.12	0.89	0.001	0.003	100	500	3000	4.0E+04	0.025		500	N/A	1 - 6 µs 0 - 2 Hz single-shot	by request	YES	≤ 8 T (static) ≤ 12. 5T (static)	71.4		0.707	parallel plate waveguide	2 - 6					2000	FEL driven EPR (with seeding at 240 GHz)	FEL driven by a recirculating Electrostatic accelerator cavity dumping outcoupling available (30 ns pulsewidth / 9 ns rise time delivering 100 kW peak power)	1991	Santa Barbara, CA USA	http://sbfel3.ucsb.edu/	**UCSB - mmW FEL**
JLab IR FEL	1.9	14	21.4	158	10kW	> 1kW	10MWp		14k	~1.2	0.5 - 1			1.3 - 74 MHz	CW 1 - 10 ms single-shot		ARC					free space	80 - 150			1 mA	< 5 mA			1997	Newport News, VA, USA	https://www.jlab.org/FEL	**JLab IR FEL**
BFEL (MIR)	5	10	30	60										3.90 MHz	2 µs macropulse 1-10 Hz		station underway		30				30									Peoe (SNP), Beijing, China	http://en.wikipedia.org/wiki/Beijing_Free_Electron_Laser	**BFEL (MIR)**
BFEL (FIR)	50	90	5	15										3.90 MHz	4 µs macropulse, 1-10 Hz 1-115 ps		station underway		90				90									Peoe (SNP), Beijing, China	http://en.wikipedia.org/wiki/Beijing_Free_Electron_Laser	**BFEL (FIR)**
ISIR FEL (Osaka U)	35	150	2	8.5	0.2	0.55		250	350	~ 2 - 20 (tentative)	8.5% (FWHM) - zero detuning 2.8% - 10um detuing at 70 um		70 - 80	27 MHz	4 - 5.5 us macropulse 10 Hz max.	YES	YES	NO	60		0.01 - 1.55 (rms)	concentric cavity	15					< 2400	FEL based on an L-band linac with a thermionic cathode		1994	Osaka, Japan		**ISIR FEL (Osaka U)**
KAERI (mmW FEL)	1000	3000	0.1	0.3										2.8 GHz	10 µs macropulse 10 Hz max.		under construction																**KAERI (mmW FEL)**
KAERI (FIR FEL)	100	200	1.5	3	0.0005	0.002	2	0.01	0.02	1.0E+01	0.3	0.01	110	2.8 GHz	3 µs macropulse 20 Hz	by request	YES		25		1 - 1.6	parallel plate waveguide	5 - 6.5				0.004	40 - 50			1999	Yusong, Taejon, Korea	https://doi.org/10.1016/S0168-9002(01)01533-9	**KAERI (FIR FEL)**
KAERI (IR FEL)	360	800	0.4	1	0.1	0.3	2	0.1	0.3	180	1			2.8 GHz	3 µs macropulse 10Hz max.		under construction		18		1.8 - 2.3	hybrid waveguide	9				0.05	40	FEL driven by an Energy Recovery Linac			Yusong, Taejon, Korea	https://accelconf.web.cern.ch/accelconf/f07/PAPERS/MOPPH046.PDF	**KAERI (IR FEL)**
FEL-TUS (MIR)	5	14	21.4	60					6	1	~ 1			2.9 GHz	2 µs macropulse 5 Hz		YES		32				≤ 40								2000	Tokyo, Japan	http://www.ri.noda.tus.ac.jp/fel-tus/English/E-Top.html	**FEL-TUS (MIR)**
FEL-TUS (FIR)	20	140	2	15			1000			10				108 MHz	1 µs macropulse 10 Hz		station underway		38		0.81 - 1.14		12.5 - 20.5						The current status of this FEL is unknown		2010	Tokyo, Japan	http://www.ri.noda.tus.ac.jp/fel-tus/English/E-Top.html	**FEL-TUS (FIR)**
LEBRA NIR FEL	1.16	6.13	49	258						~ 0.2			2		20 µs macropulse 12.5 Hz		YES (2011)		48		≤ 1.35		30 - 125					200			2001	Tokyo, Japan	https://accelconf.web.cern.ch/accelconf/f07/PAPERS/MOPPH046.PDF	**LEBRA NIR FEL**
JAERI-ERL FEL	22 µm diamond-turned SHG quartz-rod range extension										0.37 / 1MW			10.3 MHz	77 pulsed mode		Kr photoinjection)		19				17						FEL driven by an Energy Recovery Linac		2003	Tokai, Japan	https://doi.org/10.1016/S0168-9002(03)00858-0	**JAERI-ERL FEL**
KU-FEL	3.6	23	13	83.3				0.5	2 13	0.7	3			2.86 GHz 29.75 MHz	2 µs macropulse 1 - 2 Hz	YES	YES		33		≤ 1.35		19 - 40					100	Two types of e- guns: thermionic (upper value) photocathode (lower value)		2008	Kyoto, Japan	https://doi.org/10.1016/j.phpro.2016.11.009	**KU-FEL**
CAEP THz FEL	100	300	1	3										54.17 MHz	CW (planned) 5 Hz		YES		38			full waveguide	6 - 8						SRF linac driven FEL		2017	Chengdu, China	http://dx.doi.org/10.1109/IRMMW-THz.2015.7327884	**CAEP THz FEL**
Osaka FEL (NIR)	1	6	50	300		3	15000			~ 5 ps				22.3 MHz	24 µs macropulse 10 Hz		YES		3.8		0.5 - 1.4		≤ 75					27				Osaka, Japan	http://www.fel.eng.osaka-u.ac.jp/	**Osaka FEL (NIR)**
Osaka FEL (MIR)	5	22	13.6	60		1	5000			~ 5 ps				22.3 MHz	24 µs macropulse 10 Hz		YES		3.4		0.5 - 1.5		≤ 30					27				Osaka, Japan	http://www.fel.eng.osaka-u.ac.jp/	**Osaka FEL (MIR)**
Osaka FEL (FIR 1)	20	60	5	15		1	5000			~ 5 ps				22.3 MHz	24 µs macropulse 10 Hz		YES		9		1 - 2.7		≤ 30					27				Osaka, Japan	http://www.fel.eng.osaka-u.ac.jp/	**Osaka FEL (FIR 1)**
Osaka FEL (FIR 2)	50	100	3	6		1	5000			~ 5 ps				89.3 MHz	10 µs macropulse 10 Hz		YES		8		1 - 2.3		≤ 20						RF photo-gun e- source			Osaka, Japan	http://www.fel.eng.osaka-u.ac.jp/	**Osaka FEL (FIR 2)**
FELCHEM	2.5			120										0.9 - 476 MHz	2 - 25 µs macropulse 1 - 10 Hz		under construction		40	50	0.5 - 1.5		25 - 40						Dedicated to research of fundamental energy chemistry			Hefei, China	http://en.wikipedia.org/wiki/List_of_electron_accelerators_in_China	**FELCHEM**
FELCHEM	400		1.5											0.9 - 476 MHz	2 - 10 µs macropulse 10 Hz		under construction		40	50		waveguide	40 - 45						Dedicated to research of fundamental energy chemistry			Hefei, China	http://en.wikipedia.org/wiki/List_of_electron_accelerators_in_China	**FELCHEM**